

Altima



Nature's Impression
open the door to luxury

TECHNICAL CHARACTERISTICS

Classification	ASTM F1700, Class III, Type B, Solid Vinyl Floor Tile
Construction	Premium LVT consisting of fiber-glass reinforced PVC, backing system, digital imaging, and polyurethane wear layer
Installation	Full Adhesion
Size	7" x 48" (177.8mm x 1219.2mm)
Overall Thickness	3.0mm
Wear Layer	20mil (0.5mm)
Edge	Beveled
Warranty	Lifetime Residential & 12 Year Commercial
Box	15 planks 34.98 ² ft (3.25 ² m) 39.5 lbs (18 kg)
Pallet	60 cartons per pallet 2,098.98 ² ft (195 ² m)
Container	16 pallets per 20' container (33,583.68 ² ft)

Environmental & Product Testing

Flammability	ASTM E648	Excellent - CRF \geq 1.03 watts/ cm ² (Exceeds NFPA Class 1 Standards)
Smoke Density	ASTM E662	Passes < 450 D ^{mc}
Slip Resistance	ASTM C1028	Excellent - 0.67 Exceeds ADA & OSHA
Static Load Limit	ASTM F970	Passes
Flexibility	ASTM F137	Passes
Resistance to Light	ASTM F1515	Excellent
Resistance to Heat	ASTM F1514	Excellent
Chemical Resistance	ASTM F925	Excellent

Kennedy
F L O O R I N G S



CERTIFIED BY
SCS Global Services