



Product Information

Usage classification	EN ISO 10874 EN 685	23 - 32 - 41		<div style="border: 1px solid black; padding: 5px;"> <p>EN 14041:2004 450-CC0013-1</p> <p>Expanded (cushioned) polyvinyl chloride floorcoverings</p> <p>EN ISO 26986 / EN 653</p> </div>
Wear-layer	EN ISO 24340 EN 429	16 mil		
Total thickness	EN ISO 24346 EN 428	2.80 mm		
Total weight	EN ISO 23997 EN 430	1950 g/m ²		
Standard widths	EN ISO 24341 EN 426	13.1 ft		
Standard lengths	EN ISO 24341 EN 426	98 ft		

Technical Information

Reaction to fire	EN 13501-1	Bfl / S1
Underfloor heating	EN 12667	Suitable
Slip resistance	DIN 51130	R10
Dimensional stability	EN ISO 23999 EN 434	≤ 0.40 %
Light stability	EN ISO 105 B02	≥ 6
Castor chair	EN ISO 4918 EN 425	Suitable
Impact sound	EN ISO 717/2	Δ Lw 17 dB
Residual indentation	EN ISO 24343-2 EN 433	≤ 0.20 mm
Dynamic coefficient of friction	EN 13893	> 0.6

Design Information

Design	Type	Installation	Register	Tile/ Plank	Size
Disa	uni	same direction	0x0	uni	
Pamplona	tile	same direction	100x100		33.33 x 50 cm
Texas Oak	wood	same direction	150x100		20 x 150 cm
Water Oak	wood	same direction	100x100		10 x 100 cm