

Maxima

 **Nature's Impression**
open the door to luxury

TECHNICAL CHARACTERISTICS

Classification	ASTM F1700, Class III, Type B, Solid Vinyl Floor Tile
Construction	Premium LVT consisting of fiber-glass reinforced PVC, backing system, digital imaging, and polyurethane wear layer
Installation	Dry Back Full Adhesion
Size	7" x 48" (177.8mm x 1219.2mm)
Overall Thickness	2.0mm
Wear Layer	12mil (0.3mm)
Edge	Square
Warranty (limited wear)	30 Year Residential & 10 Year Commercial
Box	22 planks 51.34 ² ft (4.77 ² m) 39.5 lbs (18 kg)
Pallet	60 cartons per pallet 3,080.66 ² ft (286.20 ² m)
Container	16 pallets per 20' container (49,290.51 ² ft)

Environmental & Product Testing

Flammability	ASTM E648	Pending
Smoke Density	ASTM E662	Pending
Slip Resistance	ASTM C1028	Pass
Static Load Limit	ASTM F970	Pass
Flexibility	ASTM F137	Pass
Resistance to Light	ASTM F1515	Pass
Resistance to Heat	ASTM F1514	Pass
Chemical Resistance	ASTM F925	Pass

Kennedy
FLOORINGS



CERTIFIED BY
SCS Global Services