



# TECHNICAL CHARACTERISTICS



Board: 1326 x 204 mm – Box: 8 boards (= 2,16 m<sup>2</sup>) – Pallet: 56 boxes (= 121,19 m<sup>2</sup>)

PRODUCT SPECIFICATION		CLICK 40
Total thickness	EN 428	5 mm
Wear layer	EN 429	0,40
Total weight	EN 430	6,14 kg/ m <sup>2</sup>
Surface treatment		PUR
Usage Classification	EN 685	23-32
TEST RESULTS		
Underfloor Heating	EN 12524	suitable max. 27° (80°F)
Castor chair	EN 425	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN 423	OK
Residual indentation	EN 433	< 0,10 mm
Slip resistance	DIN 51130 EN 13983	R11 class DS
Sound reduction: Impact Sound	EN ISO 717-2 (Δ Lw)	9 dB
Reflected Walking Sound	EPLF draft 021029-5 F1	*** (9,7 sone )
Light fastness	ISO 105-B02	> 6
Dimensional stability	EN 434	<0,25%
Antistatic	EN 1815	yes
Residential warranty		Lifetime
Commercial warranty		10 Year Light Commercial
Formaldehyde	EN 717-1	E1



For this and more  
please visit us at...

[kennedyfloorings.com](http://kennedyfloorings.com)

**Kennedy**  
FLOORINGS

**BEAU  
FLOR**  
we decorate your floor