

Newport I

TECHNICAL CHARACTERISTICS

Classification	ASTM F1700, Class III, Type B, Solid Vinyl Floor Tile
Construction	Premium LVT, fiber-glass reinforced virgin PVC, consisting of backing system, digital imaging, and polyurethane wear layer with medium wood grain embossing
Installation	Full Adhesion or Loose lay
Plank Dimensions	7 $\frac{1}{4}$ " x 48" (184.2mm x 1219.2mm)
Overall Thickness	5.0mm
Wear Layer	20mil (0.5mm)
Edge	Micro Beveled
Warranty	Lifetime Residential & 17 Year Commercial
Box	10 Planks
Box (area)	24.17 ² ft (2.25 ² m)
Box (weight)	45 lbs (20 kg)
Pallet	50 boxes
Pallet (area)	1,208.5 ² ft (112.25 ² m)
Container	20 Pallets (24,170)

ENVIRONMENTAL PRODUCT TESTING

Flammability	ASTM E648 EN 13501-1	Pass - CRF \geq 0.80 watts/ cm ² B _{fl} -S1
Smoke Density	ASTM E662	Pass
Slip Resistance	EN 13893	Class DS
Phthalate Content	CPSC-CH-C1001-09.3	Pass - Not Detectable
Dimensional Stability	ASTM F2199-09	Negligible - Dimensional $\Delta \leq$ -0.02%
Curling	ASTM F2199-09	Excellent - 0.0mm



Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1

 **Shamrock Surfaces**