

ALTIMA

TECHNICAL CHARACTERISTICS

Product	Dryback Luxury Vinyl Plank
Construction	Premium LVT, fiber-glass reinforced virgin PVC, consisting of backing system, digital imaging, and polyurethane coated wear layer
Installation	Full Adhesion
Plank Dimensions	7" x 48" (177.8mm x 1,219.2mm)
Overall Thickness	3.0mm
Wear Layer	20mil (0.5mm)
Surface Finish	Medium Wood Grain Embossing
Edge	Micro Bevel
Residential Warranty	Lifetime
Commercial Warranty	15 Years
Box	15 Planks
Box (area)	34.98 ² ft
Box (weight)	39.5 lbs
Pallet	60 Boxes / 2,098.98 ² ft
Container	20 Pallets / 41,979.6 ² ft

ENVIRONMENTAL PRODUCT TESTING

Flammability	ASTM E648	Class 1 - CRF \geq 1.03 watts/ cm ²
Smoke Density	ASTM E662	Pass < 450 D _{mc}
Slip Resistance	ASTM C1028	0.67 - Exceeds ADA & OSHA
Flexibility	ASTM F137	Pass - Not Detectable
Resistance to Light	ASTM F1515	Excellent
Resistance to Heat	ASTM F2199-09	Excellent
Chemical Resistance	ASTM F925	Excellent



CERTIFIED BY
SCS Global Services

Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1

