

# EMBRACE

## TECHNICAL CHARACTERISTICS

Product	Loose Lay Luxury Vinyl Plank
Construction	Premium LVT, fiber-glass reinforced virgin PVC, consisting of backing system, digital imaging, and polyurethane coated wear layer
Installation	Full Adhesion or Loose lay
Plank Dimensions	9" x 60" (228mm x 1524mm)
Overall Thickness	5.0mm
Wear Layer	20mil (0.5mm)
Surface Finish	Embossed in Register
Edge	Micro Bevel
Residential Warranty	Lifetime
Commercial Warranty	15 Years
Box	8 Planks
Box (area)	29.92 <sup>2</sup> ft
Box (weight)	59.6 lbs
Pallet	50 boxes / 1,496 <sup>2</sup> ft
Container	20 Pallets / 29,920 <sup>2</sup> ft

## ENVIROMENTAL PRODUCT TESTING

Flammability	ASTM E648 EN 13501-1	Pass - CRF $\geq$ 0.80 watts/ cm <sup>2</sup> B <sub>fl</sub> -S1
Smoke Density	ASTM E662	Pass
Slip Resistance	EN 13893	Class DS
Phthalate Content	CPSC-CH-C1001-09.3	Pass - Not Detectable
Dimensional Stability	ASTM F2199-09	Negligible - Dimensional $\Delta \leq$ -0.02%
Curling	ASTM F2199-09	Excellent - 0.0mm



CERTIFIED BY  
SCS Global Services

### Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1

