

Newport I

TECHNICAL CHARACTERISTICS

Product	Loose Lay Luxury Vinyl Plank
Construction	Premium Luxury Vinyl, consisting of fiber-glass reinforced virgin PVC, backing system, digital imaging, and polyurethane coated wear layer
Installation	Full Adhesion or Loose lay
Plank Dimensions	7.25" x 48" (184.15mm x 1219.2mm)
Overall Thickness	5.0mm
Wear Layer	20mil (0.5mm) PU Coated
Finish	Medium Wood Grain Embossing
Edge	Micro Beveled
Residential Warranty	Lifetime Residential
Commercial Warranty	15 Year Commercial
Box	10 Planks
Box (area)	24.17 ² ft (2.25 ² m)
Box (weight)	48.5 lbs (22 kg)
Pallet	50 boxes / 1,208.3 ² ft
Container	20 Pallets / 24,167 ² ft

ENVIRONMENTAL PRODUCT TESTING

Flammability	DIN EN 13501	B _{fl}
	ASTM E648	CRF ≥ 11 kW/ m ²
	NFPA 253 Life Safety	Exceeds Class 1
Slip Resistance	DIN EN 13893	Class DS
Dimensional Stability	ASTM F2199-09	-0.02% Excellent
Curling	ASTM F2199-09	0.0mm
Phthalates	CPSC-CH-C1001-09	Pass - Not Detectable



CERTIFIED BY
SCS Global Services

Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1

