

# WPC

# ASCOT ELDORA

## TECHNICAL CHARACTERISTICS

Product	WPC (Water Proof Core)	
Construction	Product consists of WPC core with UNILIN locking system with top vinyl layer containing digital imaging, wear layer, and poly urethane coating.	
Warranty	25 Year Residential & 10 Year Light Commercial	
Wear Layer	12mil (0.3mm) PU Coated	
Surface Finish	EIR (Embossed in Register)	
Edge	Micro Bevel	
Installation	UNILIN Angle Tap Click	
	<b>ASCOT</b>	<b>ELDORA</b>
Plank Dimensions	7" x 48" (180mm x 1,220mm)	9" x 60" (228mm x 1,524mm)
Thicknesses	1.5mm Vinyl / 4mm WPC	1.5mm Vinyl / 4.5mm WPC
Overall Thickness	5.5mm	6mm
Box	10 Planks / 23.64 <sup>2</sup> ft	8 Planks / 29.9 <sup>2</sup> ft
Pallet	65 Boxes / 1,536 <sup>2</sup> ft	64 Boxes / 1,915 <sup>2</sup> ft
Container	20 Pallets	20 Pallets

## ENVIRONMENTAL PRODUCT TESTING

Flammability	ASTM E648 EN 13501-1	CRF $\geq$ 11 kW/ m <sup>2</sup> B <sub>i</sub> -S1
Smoke Density	ASTM E662	Pass
Slip Resistance	EN 13893	Class DS
Phthalate Content	CPSC-CH-C1001-09.3	Pass - Not Detectable
Dimensional Stability	ASTM F2199-09	Negligible - Dimensional $\Delta \leq$ -0.02%
Curling	ASTM F2199-09	Excellent - 0.0mm
Impact Insulation Class	ASTM 989-12	Eldora - 53 / Ascot - 52 (with Shamrock Surfaces underlayment)
Sound Transmission Class	ASTM E413-10	Eldora - 50 / Ascot - 50 (with Shamrock Surfaces underlayment)



CERTIFIED BY  
SCS Global Services

### Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1



[www.kennedyfloorings.com](http://www.kennedyfloorings.com)  
[support@kennedyfloorings.com](mailto:support@kennedyfloorings.com)  
Toll Free: (800) 665.7424

151 Paramount rd.  
Winnipeg, Manitoba  
Canada, R2X2W6

**Kennedy**  
FLOORINGS