

Oasis

SPC TECHNICAL CHARACTERISTICS

Product	SPC (Stone Poly Core)
Construction	SPC consisting of virgin limestone and polymers, with digital imaging and wear layer layered on top, backed with EVA foam backing system
Installation	Floating 2G Fold Down Click
Plank Dimensions	7" x 48" (182mm x 1240mm)
Thicknesses	3.2mm Core & 1.5mm Backing
Overall Thickness	4.7mm
Wear Layer	12mil (0.3mm) PU Coated
Finish	Medium Wood Grain Embossing
Edge	Micro Bevel
Residential Warranty	20 Years
Commercial Warranty	7 Years
Box	12 Planks
Box (area)	29.15 ² ft
Box (weight)	42 lbs
Pallet	55 Boxes
Pallet (area)	1,603.25 ² ft
Container	20 Pallets (32,065 ² ft)

ENVIRONMENTAL & QUALITY TESTING

Flammability	ASTM E648	N/A - Awaiting test results
Castor Chair	EN 425:2002	No Visible Damage
Slip Resistance	DIN 51130	R10
Residual Indentation	ASTM F1914	Pass - 8% Residual Compression
Dimensional Stability	ASTM 2199-09	Pass (less than 0.1% change)
Phthalate Content	ASTM D3421-75	Not Detected (<MDL)
Impact Insulation Class	ASTM E989-06	IIC = 72
Sound Transmission Class	ASTM E413-10	STC = 70



Setting the standard for sustainability™

FloorScore is a voluntary, independent certification program by SCS Global that tests and certifies hard surface flooring materials to ensure that they are in compliance with stringent indoor air quality emissions.

Meets CDPH/EHLB Standard Method V1.1

