RESILIENT **DESIGN**

flexitec

arterra

SPECIFICATIONS

Construction: Sheet Vinyl

Recommended Usage:
Residential and / or Commercial

Thickness: 86 mil

Wear Layer: 16 mil

Wear Layer Treatment: SuperGuard

Warranty
20 Yr Limited Residential / 10 Yr Light Commercial

Made in USA

Banksee
D001V | 599

Kahlo
D001V | 598

Kahlo
D001V | 574

Popova
D001V | 595

Serra
D001V | 593

Serra
D001V | 577

FEATURES & BENEFITS

Waterproof · Seamless · Resilient · High Variation · Stain Resistant · Easy to Clean · Easy to Maintain · Scratch Protection · Approved for Any Level

iVC RESILIENT DESIGN flexitec

arterra

CONSTRUCTION



SuperGuard Stain Shield
Provides protection against your toughest stains. Scuff- and scratch-resistant, it's built to repel just about anything - making cleaning a snap.

QuickClean Wear Layer
Easy as 1, 2, 3...
1. Easy to clean - repels dirt and grime so cleaning is a breeze.
2. Easy to maintain - resists cuts, dents, scrapes and scratches.
3. Protection - protects against day-to-day wear for long lasting beauty.

Design Layer
Where the high-definition designs and colors come to life.
A multitude of print cylinders create the most realistic visuals in the market.

Fiberglass
The fiberglass core is encapsulated by PVC layers, providing strength with flexibility, while ensuring an easy and trouble-free installation process. This inner layer offers your floor unique dimensional stability, which means no cracking, curling, expanding, or contracting.

ComfortFoam Backing
ComfortFoam is a cushioned backing that provides the ultimate foundation for support and durability. This backing reduces impact noise and sound transmission while guaranteeing unmatched comfort underfoot. It also provides resistance to mold and mildew.

SEAM SEALER & ADHESIVES

Item	Description	Style
Flex-Prim	Primer/sealer for dusty substrates	IC04
Flex-Seam	Sheet vinyl seam sealer (100LF)	FLXSD
Flex Tech Ultra	1 Gal- 99% RH adhesive (Covers 250-350 SF)	DFTUL
Flex Tech Ultra	4 Gal-99% RH adhesive (Covers 1,000-1,400 SF)	DFTUL

TESTING INFORMATION

ASTM F1303	Type 1, Grade 2
Static Load Limit | ASTM F970	750 psi
Smoke Density | ASTM E662	<450
COF Slip | ASTM C1028	0.64
Residual Indentation | ASTM F1914	0.002
Flexibility | ASTM F137	Passes (6 mm)
Flooring Radiant Panel | ASTM E648	Class 1
Dimensional Stability with Heat | ASTM F2199	0.10%
Resistance to Heat | ASTM F1514	Passes
Resistance to Light | ASTM F1515	Passes
Resistance to Chemicals | ASTM F925	Passes