

# level plus collection

property management seamless flooring



## Designs



Chaconne | 532  
U9580.119K532P144



Chaconne | 592  
U9580.119K592P144



Bamboo | 593  
U3240.119K593P144



Laredo | 882  
U5370.119K882P144



Bonnette | 934  
U6160.119K934P144



Highland | 737  
U5300.119K737P144



Luxor | 846  
U2360.119K846P144



Bongo | 847  
U3950.119K847P144

# level plus collection

property management seamless flooring



## Designs



Manday | 552  
U8205.119K552P144



Manday | 875  
U8205.119K875P144



Manday | 876  
U8205.119K876P144



Manday | 877  
U8205.119K877P144



Sebrian | 593  
U6230.119K593P144



Applegate | 567  
U8267.119K567P144



Beacon | 531  
U6030.119K531P144



Manday | 595  
U8205.119K595P144



Washington | 933  
U9480.119K933P144



Manday | 804  
U8205.119K804P144



Manday | 829  
U8205.119K829P144



Nice | 858  
U1070.119K858P144

# level plus collection

property management seamless flooring



## Specifications

Construction	Recommended Usage	Thickness	Wear Layer	Wear Layer Treatment	Finish	Width	Standard Length	Average Weight of Standard Roll	Warranty
Sheet Vinyl	Residential	65 Gauge	10 mil	SuperGuard	Mechanically Embossed	12'	150 lineal ft	520 lbs	10-Year Limited Property Management*

\* See written limited warranty for full details.

## Testing Information

ASTM 1303.....	Type 1, Grade 3
Residual Indentation   ASTM F1914.....	0.006
Flexibility   ASTM F137.....	Passes (10 mm)
Resistance to Heat   ASTM F1514.....	Passes
Resistance to Light   ASTM F1515.....	Passes
Resistance to Chemicals   ASTM F925.....	Passes
Sound Transmission/Impact Insulation   ASTM E492.....	IIC 55
Critical Radiant Flux   ASTM E648.....	Class I
Static Coefficient of Friction   C1028-96.....	Passes (Dry .77/Wet .77)
Smoke Density (flaming)   ASTM E662-03.....	Passes 450 or less
Smoke Density (non-flaming)   ASTM E662-09.....	Passes 450 or less



Made in the USA



CERTIFIED BY SCS Global Services

# level plus collection

property management seamless flooring



## Adhesives

- **Flex Tech PSA for Sheet Vinyl**

**1 Gallon** 706471 | **4 Gallon** 706472 | **1 Quart** 706473

**Coverage** 350 sq ft/gallon - porous | 400 sq ft/gallon - non porous

Pressure sensitive adhesive | Clear set | Solvent free

- **Flex Seam Bond**

**8 oz.** 706474

Solvent free | Low VOC | High strength | Fast drying | Dries clear

- **Flex Prim Acrylic Latex Primer**

**1 Gallon** 706475

**Coverage** Up to 500 sq ft/gallon

Use as primer coat | Increases adhesive performance | Increases adhesive coverage

- **Acrylic Duck Tape Roll**

**1 Gallon** 706092

**Coverage** 2" x 50'

Acrylic tape | Perfect for no-glue fiberglass backed vinyl flooring

- **iGrip Adhesive VINYL**

**1 Gallon** 706620 | **4 Gallon** 706621

**Coverage** 350 sq ft/gallon - porous | 400 sq ft/gallon - non porous

Permanent adhesive | Commercial wet set adhesive | Combats mold/mildew growth | Greenguard certified | low VOCs

- **iGrip Adhesive Spray**

**22 oz.** 706904

**Coverage** approximately 140 sq ft

Permanent adhesive | Highly aggressive | Recommended for sheet vinyl | Can be used in occupied buildings

- **Infuze Seam Sealer**

**5 fl. oz.** 706662

**Coverage** up to 150 lineal ft

Commercial seam sealer designed to seal all seems in Itec commercial sheet