

# level ten collection

property management seamless flooring



## Designs



Andorra | 591  
U3170.212K591G144



Aspin | 551  
U3890.212K551G144




Aspin | 583  
U3890.212K583G144



Sandridge Slate | 594  
U5330.212K594G144



Riche | 545  
U2720.212K545G144



Baron | 731  
U6580.212K731G144



Toucan | 536  
U4290.212K536G144



Biscay | 538  
U3680.212K538G144

# level ten collection

property management seamless flooring



## Designs



Cezanne | 531  
U8203.212K531G144



Baron | 713  
U6580.212K713G144



Condor | 573  
U3140.212K573G144




Nice | 563  
U1070.212K563G144



Nice | 564  
U1070.212K564G144



Chasen | 932  
U6920.212K932G144



Diago | 544  
U4340.212K544G144



Burlington | 565  
U3680.212K565G144



Condor | 564  
U3140.212K564G144

# level ten collection

property management seamless flooring



## Specifications

Construction	Recommended Usage	Thickness	Wear Layer	Wear Layer Treatment	Finish	Width	Standard Length	Average Weight of Standard Roll	Warranty
Sheet Vinyl	Residential	55 Gauge	10 mil	QuickClean	Mechanically Embossed	12'	150 lineal ft	456.2 lbs	5-Year Limited Property Management*

\* See written limited warranty for full details.

## Testing Information

ASTM 1303.....	Type 1, Grade 3
Residual Indentation   ASTM F1914.....	0.006
Flexibility   ASTM F137.....	Passes (10 mm)
Resistance to Heat   ASTM F1514.....	Passes
Resistance to Light   ASTM F1515.....	Passes
Resistance to Chemicals   ASTM F925.....	Passes
Sound Transmission/Impact Insulation   ASTM E492.....	IIC 54
Critical Radiant Flux   ASTM E648.....	Class I
Static Coefficient of Friction   C1028-96.....	Passes (Dry .80/Wet .80)
Smoke Density (flaming)   ASTM E662-03.....	Passes 450 or less
Smoke Density (non-flaming)   ASTM E662-09.....	Passes 450 or less



# level ten collection

property management seamless flooring



## Adhesives

- **Flex Tech PSA for Sheet Vinyl**

**1 Gallon** 706471 | **4 Gallon** 706472 | **1 Quart** 706473

**Coverage** 350 sq ft/gallon - porous | 400 sq ft/gallon - non porous

Pressure sensitive adhesive | Clear set | Solvent free

- **Flex Seam Bond**

**8 oz.** 706474

Solvent free | Low VOC | High strength | Fast drying | Dries clear

- **Flex Prim Acrylic Latex Primer**

**1 Gallon** 706475

**Coverage** Up to 500 sq ft/gallon

Use as primer coat | Increases adhesive performance | Increases adhesive coverage

- **Acrylic Duck Tape Roll**

**1 Gallon** 706092

**Coverage** 2" x 50'

Acrylic tape | Perfect for no-glue fiberglass backed vinyl flooring

- **iGrip Adhesive VINYL**

**1 Gallon** 706620 | **4 Gallon** 706621

**Coverage** 350 sq ft/gallon - porous | 400 sq ft/gallon - non porous

Permanent adhesive | Commercial wet set adhesive | Combats mold/mildew growth | Greenguard certified | low VOCs

- **iGrip Adhesive Spray**

**22 oz.** 706904

**Coverage** approximately 140 sq ft

Permanent adhesive | Highly aggressive | Recommended for sheet vinyl | Can be used in occupied buildings

- **Infuze Seam Sealer**

**5 fl. oz.** 706662

**Coverage** up to 150 lineal ft

Commercial seam sealer designed to seal all seems in Itec commercial sheet