



Shamrock Surfaces

PRODUCT

THICKNESS

WEAR LAYER

INSTALLATION

FINISH

EDGE

BOX

PALLET

PLANK DIMENSIONS

OVERALL THICKNESS

STONE CORE PLANK CONSISTING OF EVA ATTACHED PAD, EXTRUDED LIMESTONE AND POLY CORE, HIGH DEFINITION IMAGING, AND EIR FINISHED POLYURETHANE COATED WEAR LAYER 7¹/₄" X 48" (184MM X 1,220MM) 4.0MM STONE CORE + 1.0MM EVA ATTACHED PAD 5.0MM 12MIL (0.3MM) EMBOSSED IN REGISTER MICRO BEVEL FLOATING 14F CLICK 10 PLANKS / 24.16 FT² 50 BOXES / 1,208.14 FT² 20 YEARS 7 YEARS

RESIDENTIAL WARRANTY LIGHT COMMERCIAL WARRANTY

FLOOR SCORE CERTIFIED TO MEET INDOOR AIR QUALITY STANDARDS, RIGOROUSLY TESTED TO BE FREE OF 35 TYPES OF VOLATILE ORGANIC COMPOUNDS INCLUDING FORMALDEHYDE. QUALIFIES FOR MANY GREEN BUILDING SCHEMES SUCH AS LEED V4, WELL, BREEAM, & CHPS.

WWW.KENNEDYFLOORINGS.COM/OASIS



DAYTONA OAK

VERMONT OAK

AUGUSTINE OAK

BERMUDA OAK

CORAL OAK