











Product information

European classification	EN ISO 10874	Domestic Moderate Commercial General
Total thickness	EN ISO 24346	ca. 2,00 mm
Wearlayer	EN ISO 24340	ca. 0,50 mm
Wear layer treatment		HyperGuard+
Total weight	EN ISO 23997	ca. 2.358 g/m²















Sliprestraint DIN 51130 R10 Inflammability EN 13501 Bfl-S1 Acoustical insulation EN 717 ΔLw 16 dB Underfloor heating EN 12524 Suitable Thermal conductivity EN 12524 0,25 W/mK Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good			
Inflammability EN 13501 Bfl-S1 Acoustical insulation EN 717 ΔLw 16 dB Underfloor heating EN 12524 Suitable Thermal conductivity EN 12524 0,25 W/mK Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good	Slip resistance	EN 13893	DS
Acoustical insulation EN 717 ΔLw 16 dB Underfloor heating EN 12524 Suitable Thermal conductivity EN 12524 0,25 W/mK Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good	Sliprestraint	DIN 51130	R10
Underfloor heating EN 12524 Suitable Thermal conductivity EN 12524 0,25 W/mK Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good	Inflammability	EN 13501	Bfl-S1
Thermal conductivity EN 12524 0,25 W/mK Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good	Acoustical insulation	EN 717	ΔLw 16 dB
Thermal resistance EN ISO 12466 0,0158 m²K/W Resistance to household chemicals EN ISO 26987 Very good	Underfloor heating	EN 12524	Suitable
Resistance to household chemicals EN ISO 26987 Very good	Thermal conductivity	EN 12524	0,25 W/mK
	Thermal resistance	EN ISO 12466	0,0158 m ² K/W
Warranty (Commercial use) 5 years	Resistance to household chemicals	EN ISO 26987	Very good
	Warranty (Commercial use)		5 years

Technical information

Premium strength and embossed backing

The Tempo quality brings you the confidence of a floor made for **business** and home office spaces. The super compact backing is known for its premium strength and the waffle structured emboss on the backing guarantees strong adhesion to the subfloor.

This collection features an impressively though wear layer that is capable of dealing with the high levels of footfall encountered in these areas. Tempo is the ultimate multi-layer heterogeneous vinyl floor. Bringing versatile design to projects through wide-ranging wood and stone designs.

Tough yet stylish

A strong floor is key in any room but what we really want is a floor that looks good.

Stylish, pretty and fitting the interior. Stop reading and discover these beautiful designs yourself!

It will be difficult to pick one though. Our designers did their very best, you will love them all!

Kids, pets, mud or snow: your floor is ready for the challenge!

Our Hyperguard+ protection layer (PU Lacquer) will protect your floor in every situation. Kids, pets, muddy snow shoes, chairs: your floor will be super easy to maintain. This protection layer will make your life simple and easy.

A high performance multi-layer floor

